



# ECO CANVAS 2T / 3T

HIGH PERFORMANCE WELDING PROTECTION CANVAS

ECO CANVAS is a high temperature protection canvas designed to shield people, equipment and structures from welding sparks, molten metal splash and extreme heat.



HIGH TEMPERATURE  
RESISTANCE



MOLTEN METAL  
PROTECTION



EXCELLENT  
DURABILITY



KFI  
APPROVED

## KEY FEATURES

- Withstands extreme heat up to over 1,300°C
- Ceramic coating for superior heat and flame resistance
- Excellent bending durability and long service life
- Prevents penetration of molten metal and sparks
- KFI (Korea Fire Institute) Approved

## TYPICAL APPLICATIONS



WELDING



CUTTING



SHIPBUILDING  
& OFFSHORE



INDUSTRIAL  
FACILITIES

## TECHNICAL DATA

| MODEL            | MATERIAL<br>(STRUCTURE)                                                  | GSM<br>(g/m <sup>2</sup> ) | COATING | TEMPERATURE<br>RESISTANCE                   | BENDING<br>DURABILITY | TOTAL<br>WEIGHT | WIDTH | LENGTH | APPROVAL |
|------------------|--------------------------------------------------------------------------|----------------------------|---------|---------------------------------------------|-----------------------|-----------------|-------|--------|----------|
| ECO CANVAS<br>2T | Carbon Felt (1.25mm)<br>+<br>Canvas (0.5mm)                              | 710                        | Ceramic | Up to 1,300°C<br>(2,372°F)<br>Not Penetrate | Very Good             | 16kg / Roll     | 1m    | 20m    | KFI      |
| ECO CANVAS<br>3T | Carbon Felt (1.25mm)<br>+<br>Canvas (0.5mm)<br>+<br>Carbon Felt (1.25mm) | 1,030                      | Ceramic | Over 1,300°C<br>(2,372°F)<br>Not Penetrate  | Very Good             | 22kg / Roll     | 1m    | 20m    | KFI      |

Note: The above values are typical results from standard production.  
They may vary depending on actual conditions.